

SPECIFICATIONS

Model No.	NA31-210A	NA32-260A
Heating Capacity at Air 20°C / 15°C, Water Temperature from 15°C to 55°C		
Heating Capacity (kW)	2.9	2.9
Power Input (kW)	0.67	0.67
COP	4.33	4.33
Power supply	220V~240V / 50HZ / 1phase	220V~240V / 50HZ / 1phase
Heat Pump Max. Power Input (W)	1050	1050
Heat Pump Max. Current (A)	5.00	5.00
Electric Heater Power (W)	1500	1500
Electric Heater Current (A)	8.00	8.00
Power Supply	220V~240V / 50Hz	220V~240V / 50Hz
Refrigerant	R290 / 400g	R290 / 400g
Net Dimension (mm)	Φ620×1582	Φ620×1809
Package Dimension (mm)	700×700×1722 (with pallet)	700×700×1952 (with pallet)
Net Weight (Kg)	107	119
Gross Weight (Kg)	125	138
Noise (dB)	42	42
Water tank volume (L)	210	260
Working temperature range (°C)	-7~43	-7~43

OPERATIONAL MODES

MODE	TEMP RANGE	MAX TEMP HEAT PUMP	MAX TEMP ELEMENT
STAN	15°C ~ 60°C	60°C	-
ECO	15°C ~ 60°C	60°C	-
HYB	15°C ~ 70°C	60°C	70°C
ELE	15°C ~ 70°C	-	70°C

Our extensive 6 year warranty gives you peace-of-mind knowing that all system parts are covered.
The labor is covered for 1 year after the installation date.

*This is a guide only. Site specifics and flow rates of fixtures will have an impact on performance.

SIZING GUIDE

210L	1-3 people
260L	3-5 people

